

NEC P401W

Order Code: 60003693

NEC Professional Desktop Projector



Perfect for mid to large meeting rooms as well as classrooms in higher education where semi-professional high brightness performance is required, the P401W is a very bright and compact wide format projector is recommended for screen sizes of up to 130". Thanks to the compact design, large optical zoom of 1.7x, vertical lens shift and vertical and horizontal keystone correction, flexible integration into any room is a reality, saving unnecessary installation costs.

Customers that need advanced connectivity benefit from remote control and monitoring over wired and wireless (optional) network, also content transmission including audio is supported. An optional adapter for Intel® WiDi even allows high quality video and audio transmission in excellent quality. A large number of input options allow you to connect all types of digital and analogue input signals.

BENEFITS

Affordable Large Screen projection - ideal for larger corporate or education venues and auditoriums.

Full Connectivity and Media Playback - stay up to date with today's playback demands with a wide range of interfaces and assured playback of all major media formats.

Professional and Flexible Installation - versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.

Free DisplayNote Multiuser Licence - present, share, collaborate with up to 5 participants across multiple devices (available until May 2015).



ERP
COMPLIANT



NaViSet
Administrator 2



| | | |
|-----------------------------|---|---|
| IMAGE | Projection Technology | 3 x 1.5 cm (0.59") LCD Panel with MLA |
| | Native Resolution | 1280 x 800 (WXGA) |
| | Contrast Ratio ¹ | 4000:1 |
| | Brightness ¹ | 4000 High Bright / 3300 Normal / 2680 Eco ANSI Lumens |
| | Lamp | 240 W UHP AC |
| | Lamp Life [hrs] | 6000 Eco / 5000 Normal / 4000 High Bright Mode |
| | Lens | F= 1.7~2.2, f= 17.4~29 mm |
| | Lens shift | Vertical lens shift 0 - 0.6 |
| | Keystone correction | manual H/V +/-30° |
| | Projection Factor | 1.3 - 2.2 : 1 |
| | Projection Distance [m] | 0.7 - 14.6 |
| | Screen Size (diagonal) [cm] / [inch] | Maximum: 762 / 300"; Minimum: 64 / 25" |
| | Zoom | 1 - 1.7; Manual |
| | Focus Adjustment | Manual |
| | CONNECTIVITY | Supported Resolutions |
| Frequency | | Horizontal: 15~100 kHz (RGB: 24 kHz); Vertical: 50 - 120 Hz |
| RGB (analog) | | Input: 1 x Mini D-sub 15 pin Output: 1 x Mini D-sub 15 pin |
| HDMI™ | | Input: 2 x HDMI™ (Deep Color, Lip sync) with HDCP |
| Video | | Input: 1 x RCA |
| S-Video | | Input: 1 x Mini DIN 4-pin |
| Audio | | Input: 1 x 3.5 mm Stereo Mini Jack; 1 x 3.5 mm Stereo Mini Jack for Computer analog; 1 x RCA Stereo for Video and S-Video; 2 x HDMI audio Output: 1 x 3.5 mm Stereo Mini Jack (variable) |
| Control | | Input: 1 x D-Sub 9 pin (RS-232) (male) |
| LAN | | 1 x RJ45 |
| USB | | 1 x Type B; 2 x Type A (USB 2.0 high speed) |
| Video Signals | NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM | |
| REMOTE CONTROL | Remote Control | Aspect Ratio; Audio Control; Auto Adjust; Eco Mode Control; Freeze-function; Help-function; ID set; Keystone Correction; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Presentation and Mouse Control; Select (up, down, left, right); Source Select |
| ELECTRICAL | Power Supply | 100-240 V AC; 50 - 60 Hz |
| | Power Consumption [W] | 325 (High Bright) / 274 (Normal) / 231 (Eco) / 10 (Stand-by) / 2.8 (Network Stand-by) / 0.4 (Power Savings Mode) |
| MECHANICAL | Dimensions (W x H x D) [mm] | 398 x 115 x 282 (without lens and feet) |
| | Weight [kg] | 4.1 |
| | Fan Noise [dB (A)] | 29 / 36 (Eco / Normal) |
| ERGONOMICS | Safety and Ergonomics | CE; ErP; RoHS; TÜV GS |
| | Speakers [W] | 1 x 16 (mono) |
| ADDITIONAL FEATURES | Special Characteristics | Auto Eco Mode; Auto Power ON/OFF; Carbon Savings Meter; Contrast Ratio 4000:1 with Iris; Control ID Function; DICOM Simulation; Direct Power-Off Function; Geometric correction by software; Help Function; HTTP Browser Control; Kensington security slot; Keypad Lock; Lens Cover; Lens Shift, vertical +60 %; Magnify; Manual Wall Color Correction; Mouse Control with USB Display; NaViSet Administrator 2; Off-Timer; Optional User Logo; OSD with 27 languages; Password Security System; Pincushion Correction; Plug&Play W-LAN Option; Quick Start; Remote Desktop; Source Select with Beep Function; Test Pattern; Timer-Function; Unique Power Saving Functions; USB Display including Audio; USB Viewer; Virtual Remote for direct PC control; Windows 7 Network Projector; Windows Media Connect Function; Windows Network Drive |
| GREEN FEATURES | Energy Efficiency | 0.4W Power save mode; 40% AV mute function; Auto ECO Mode; Green one touch ECO and AV mute button |
| | Ecological Materials | Downloadable manuals; ECO packaging |
| | Ecological Standards | ErP compliant; RoHs compliant |
| WARRANTY | Projectors | 3 years pan-European service |
| | Lamp | 6 months, max. 1000 hrs |
| SHIPPING CONTENT | Shipping Contents | IR Remote Control (RD-448E); Mini D-SUB Signal Cable (1.8 m); Power Cord (1.8 m); Projector; Quick Setup Guide; Security Sticker; Users Manual; Utility software |
| OPTIONAL ACCESSORIES | Optional Accessories | Cable Cover (NP03CV); Free Wireless Image Utility App; Lamp (NP23LP); Universal Ceiling Mounts (NP01/02/03/04/05UCM); Wireless LAN module NP02LM2 (Europe), NP02LM3 (Russia) |

¹ Compliance with ISO21118-2005