

# NEC PX700W

Order Code: 60003828

NEC Professional Installation Projector



The PX700W a wide format dual lamp installation projector for the highest levels of heavy duty usage, unique picture quality in highest resolution and is the worldwide first projector supporting STv2, compatible with the NEC /Intel OPS standard.

The professional features make it ideal for Rental/Staging, Large Corporate, High Education, Conference Room, Museum and Signage.

## BENEFITS

**Display content that demands attention** - with WXGA resolution and superb brightness levels and colour ranges, your viewers will enjoy an outstanding visual experience.

**Installation is easy, even in challenging venues** - a motorized Lens Shift with vertical and horizontal adjustment makes setting up the perfect installation image easy.

**Simple Connectivity** - due to the vast number of connectors featured with this projector, including an innovative DisplayPort terminal and a host of networking, analog and digital connection terminals.

**Time saving network control** - for cost saving convenient maintenance and management of content and scheduling.

**Free Download of Multi-Display Management Software** - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



**NaViSet**  
Administrator 2

IMAGE	Projection Technology	1 x 1.65 cm (0.65") 2x LVDS DMD Chip
	Native Resolution	1280 x 800 (WXGA)
	Contrast Ratio <sup>1</sup>	2100:1 with DynamicBlack™
	Brightness <sup>1</sup>	7000 ANSI Lumen (approx. 80% in Eco Mode)
	Lamp	2-Lamp System (2 x 400 W AC), 2 x 320 Eco Mode
	Lamp Life [hrs]	2000 (2500 Eco Mode)
	Lens	7 optional bayonet lenses
	Lense Adjustment	Motorized
	Projection Factor	depending on lens selection (0.76:1 and 1.25-8.3:1)
	Projection Distance [m]	0.8 (NP16FL) - 54 (NP21ZL)
	Screen Size (diagonal) [cm] / [inch]	(best performance range); Maximum: 762 / 300"; Minimum: 127 / 50"
	Supported Resolutions	1920x1200 (WUXGA) - 640x480 (VGA); 1080i/60; 1080p/60; 1080i/50; 1080p/50; 720p/60; 720p/50; 576i/50; 576p/50; 480p/60; 480i/50
	Frequency	Horizontal: 15–108 kHz (RGB: 24 kHz); Vertical: 48 – 120 Hz
CONNECTIVITY	RGB (analog)	Input: 1 x 5BNC, shared with Component Signal (YPbPr); 2 x Mini D-sub 15 pin Output: 1 x Mini D-sub 15 pin
	Digital	Input: 1 x DisplayPort; 1x HDMI™ (V.1.3) supporting HDCP
	Video	Input: 1 x RCA
	S-Video	Input: 1 x Mini DIN 4-pin
	Control	Input: 1 x D-Sub 9 pin (RS-232); 1 x Network (RJ45, W-LAN optional)
	Option Slot	Input: 1 x Slot for optional STv2 or HD/SD-SDI Module
	USB	2 x Type A (USB 2.0 high speed)
REMOTE CONTROL	Input:	1 x 3.5 mm Stereo Mini Jack
	Remote Control	Aspect Ratio; Auto Adjust; Eco Mode Control; Freeze-function; Full Lense control; HDMI; Help-function; ID Select; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Select (up, down, left, right); Source Select
ELECTRICAL	Power Supply	100-240 V AC; 50 - 60 Hz
	Power Consumption [W]	0.4 Power Savings Mode; 18 Network Stand-By Mode; 405 Eco Single Lamp Mode; 494 Normal Single Lamp Mode; 753 Eco Dual Lamp Mode; 931 Normal Dual Lamp Mode
MECHANICAL	Dimensions (W x H x D) [mm]	504 x 192 x 516 (without lens and feet)
	Weight [kg]	19.7
	Fan Noise [dB (A)]	43
ERGONOMICS	Safety and Ergonomics	CE; ErP; RoHS; TÜV GS
ADDITIONAL FEATURES	Special Characteristics	2x Colourwheel; AMX Beacon; Blanking; Crestron RoomView; Digital 3D Reform™; Direct Power-Off Function; Edge Blending Function; Geometric Correction; Help Function; Hollywood Quality Video Processing for best image quality; Keystone Correction (H=±40°, V=±30°); LAN control; Lens Memory; Lens Shift (vertical 0.5 max., horizontal ± 0.1 max.); Lens Shutter; NaViSet Administrator 2; OPS module support; Optional User Logo; OSD with 27 languages; Outstanding Multimedia and Network Functions; Password Security System; PIP/Side by Side, HDMI - Input; PJ LINK; Plug&Play W-LAN Option; Powerpoint, Movie, PDF and USB Picture Viewer; RS-232 Control; Seamless Switching; SNMP; Stacking Function; Test Pattern; Windows 7 Network Projector
GREEN FEATURES	Energy Efficiency	Complete shut-off switch; Intelligent Power Management
	Ecological Materials	ECO packaging; Minimal use of harmful material
	Ecological Standards	RoHs compliant; WEEE
WARRANTY	Projectors	3 years pan-European service
	Lamp	6 months, max. 1000 hrs
SHIPPING CONTENT	Shipping Contents	Anti-theft cap for LAN Unit; Anti-theft screw for lens; Colourwheel (for exchange); IR Remote Control (RD - 455E); Power Cord; Projector; Quick Setup Guide; Stacking Holder; Users Manual on CD-ROM
OPTIONAL ACCESSORIES	Optional Accessories	Air Filter (NP02FT); Ceiling Mount Kit; HD/SD-SDI Module; Lamp (NP22LP); STv2 PC; Wireless LAN module NP02LM2 (Europe), NP02LM3 (Russia)
	Lenses	NP16FL (0.76:1); NP17ZL (1.25-1.79:1); NP18ZL (1.73-2.27:1); NP19ZL (2.22-3.67:1); NP20ZL (3.6-5.4:1); NP21ZL (5.3-8.3:1); NP31ZL (0.75-0.93:1)

<sup>1</sup> Compliance with ISO21118-2005