

LBB 1997/00 Plena Voice Alarm System Remote Control Extension

www.boschsecurity.com



BOSCH

Invented for life



- ▶ Remote control of the voice alarm routers
- ▶ EN 54-16 certified and EN 60849 compliant
- ▶ Emergency (EMG) and background music (BGM) zone selections
- ▶ EMG state and fault indicators
- ▶ One extension per router

The Plena voice alarm remote control panels allow the system to be controlled remotely from one or two remote locations. There are five models available:

- The fireman's panel, which has oversized, illuminated controls and an all-call function
- The main RC unit, which duplicates the front panel of the Voice Alarm Controller
- The RC extension, which duplicates the front panel of the router
- The main RC kit
- The RC extension kit

The kits are a functional match to the remote control and the RC extension, with connectors on the front panel instead of controls and indicators.

Functions

The extension duplicates the Plena LBB 1992/00 Voice Alarm Router front panel. One extension is needed per router, but not all routers need to have a remote control.

An LED meter shows the presence and level of the calls that are running in the system. The fault indicators show detailed information of any faults

present in the system. The unit connects to the Plena Voice Alarm System via standard shielded CAT 5 cable. The included rack mounting brackets can also mount the unit on a wall with spacing for cables at the back, as well as to a horizontal surface above or below the unit.

One or more extensions need to be connected to a voice alarm RC or voice alarm RC kit.

Certifications and approvals

Safety	acc. to EN 60065
Immunity	acc. to EN 50130-4
Emission	acc. to EN 55103-1
Emergency	acc. to EN 54-16 / EN 60849

Region	Certification	
Europe	CE	Declaration of Conformity
	CPD	
Poland	CNBOP	

Installation/configuration notes



LBB 1997/00 rear view

Parts included

Quantity	Component
1	LBB 1997/00 Plena Voice Alarm System Remote Control Extension
1	Set of 19" mounting brackets
1	1 m CAT 5 cable

Technical specifications

Electrical*

Power supply	
Voltage	24 VDC, +15% / -15%
Current typical	50 mA
Current max (indicator test)	200 mA (indicator test)
Relay contacts	30 V, 1 A

* Technical performance data according to IEC 60268-3

Mechanical

Dimensions (H x W x D)	88 x 430 x 90 mm (19 in wide, 2U high)
Weight	Approx. 2 kg
Mounting	Stand-alone, 19" rack
Color	Charcoal

Environmental

Operating temperature	-10 °C to +55 °C (14 °F to +131 °F)
Storage temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative humidity	<95%

Ordering information

LBB 1997/00 Plena Voice Alarm System Remote Control Extension

six-zone voice alarm router remote control
Order number **LBB1997/00**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com