

PRS 1AIP1 IP Audio Interface

www.boschsecurity.com



BOSCH

Invented for life



- ▶ All-in-one solution for audio transport on IP-networks
- ▶ Supervised control inputs and outputs
- ▶ Supports re-broadcasting
- ▶ Configurable audio delay on the output for loudspeaker alignment
- ▶ Easy to install and configure via standard web-browser

The PRS-1AIP1 is a universal, IP-based audio device supporting VoIP and Audio over IP applications. It is an ideal solution for bridging audio and contact closures over long distance LAN and WAN networks, e.g. in and between conference centers and/or in remote interpretation applications. It extends and interfaces to DCN systems and non-network based traditional conference and public address systems without the need for a PC during operation.

The unit has analog audio inputs and outputs for easy interfacing. One audio input can be switched to microphone sensitivity with built-in microphone supervision. Also, the control inputs offer cable and connection supervision.

Control inputs and outputs can be used to pass channel engaged events to the DCN system.

Functions

Audio

Multiple audio formats are supported: single channel, full duplex 16-bit PCM or G.711 for very low latency, and two-channel send or receive MP3 for high quality audio with various sample rates and compression settings.

The unit provides two balanced line inputs and two balanced line outputs. One of the inputs can be configured as balanced microphone input with a phantom power supply for electret / condenser microphones. The output level is configurable. A configurable audio delay can be used to artificially delay the playback of audio for loudspeaker alignment.

Audio Routing

Audio signals can be routed in uni-cast to up to 16 receivers, preconfigured or on activation of control inputs. Receivers are able to re-broadcast the incoming audio stream to other receivers. In case the interfaces are on the same LAN also broadcast is supported.

In PCM and G.711 (uLaw and aLaw) full duplex audio interfacing between two units is possible.

Control inputs and outputs

The unit has eight control inputs. Eight control outputs have dry relay contacts. Control inputs can be routed to control outputs for remote actions or to pass on fault information between audio transmitter and receiver, in both directions. Control inputs can also be configured to change the audio routing.

An additional dry relay contact is provided for fault indication of the unit, including a high temperature fault situation.

Network Interfaces

The unit interfaces to 10 and 100 Mbit Ethernet networks and announces its IP-address that was given by a DHCP server. It can also search the network for a free IP-address or can be given a static IP-address. A second Ethernet connection is available to support network redundancy.

An RS 232 interface is build-in to communicate additional serial data over the IP network.

Power Supplies

Two power supply connections are provided as main input and backup input with supervision of both supplies.

Controls and Indicators (front)

- Reset button, recessed
- Two status indicator LEDs for network
- Eight status LEDs for control inputs

Interconnections (rear)

- Eight control inputs on Euro-connector
- Eight control outputs on Euro-connector
- Fault relay output on Euro-connector
- Two balanced audio inputs on Euro-connector (one line input, one line / microphone input)
- Two balanced audio outputs on Euro-connector
- Two Ethernet connections on RJ45
- RS 232 on Sub-D
- RS 485 on Euro-connector (future use)
- Main power supply on jack
- Backup power supply on Euro-connector

Certifications and approvals

Safety	acc. to IEC 60065-98
Immunity	acc. to EN 55103-2 / EN 50130-4 / EN 55024
Emissions	acc. to EN 55103-1 / EN 55022
Emergency	acc. to EN 60849

Parts included

Quantity	Component
1	PRS-1AIP1 IP Audio Interface
1	Power supply
1	Set of connectors

Technical specifications

Electrical

External power supply 1	18 to 56 VDC
External power supply 2	18 to 56 VDC
Power consumption	8 W max
Microphone input	
Sensitivity	-48.5 to -26 dBV

Impedance	1360 ohm
Frequency response	100 Hz to 15 kHz
S/N	>60 dB
Supervision detection	Electret: 0.4 – 5 mA Dynamic: 120 – 1300 ohm
Line Inputs	
Sensitivity	-16.5 to +6 dBV
Impedance	22 kohm
Frequency response	20 Hz to 15 kHz
S/N	>70 dB
Pilot tone detection level (input 2 only)	-30 dBV
Line outputs	
Level	6 dBV max
Pilot tone level (output 2 only)	-20 dBV (20 kHz)
Audio formats	
MPEG 1-layer 3 (MP3)	32, 44.1 and 48 kHz sample rate
	Encoding up to 192 kbps VBR
	Decoding up to 320 kbps (stereo)
MPEG 1-layer 2	16, 22.05 and 24 kHz sample rate
G.711	uLaw, aLaw at 8, 24 or 32 kHz sample rate
PCM	16-bit at 8, 24 or 32 kHz sample rate
Control inputs	
Connectors	Removable screw terminals
Operation	Closing contact (with supervision)
Control / fault outputs	
Connectors	Removable screw terminals
Operation	Make contact (SPST, voltage free)
Rating	24 V, 0.5 A
Ethernet	
Connector	Dual RJ45, DTE-pinout
Standard	802.3i / 802.3u
Speed	10 / 100 Mbps, auto-negotiation
Flow	Full / half-duplex, auto-negotiation
Protocol	TCP/IP, UDP, RTP, IGMP, DHCP, SNMP

RS 232	
Connector	9-pin Sub-D male, DTE-pinout
Pinout	300 to 115.200 Baud
Setting (default)	9600, 8, N, 1

Mechanical

Dimensions (H x W x D)	216 x 38 x 125 mm(8.5 x 1.5 x 4.92 in) (half 19" wide)
Weight	0.7 kg (1.5 lb)
Mounting	Stand-alone or in 19"-rack with additional frame
Color	Silver with Charcoal

Environmental

Operating temperature	-5 °C to +50 °C (+23 °F to +122 °F)
Start-up temperature	0 °C to +50 °C (+32 °F to +122 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	15 to 90 %
Air pressure	600 to 1100 hPa

Ordering information

PRS-1AIP1 IP Audio Interface

universal, IP-based audio device supporting VoIP and Audio over IP applications.

Order number **PRS-1AIP1**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com